



GATE CONTROL GEAR

THE GATE CLOSER
SPECIALISTS

GCG2000 Easy Garden Gate Closer

In the GCG2000 Easy Garden Gate Closer you have an inexpensive gate closer for lightweight gates or doors which provides hydraulically controlled closing speed and final latching speed adjustments. This closer was designed for installation to garden gates and lightweight doors where the * gate post or door frame is flush with the gate or door and where the hinge point is at the corner of the gate post or door frame (like a typical internal house door with butt hinges).

If you are a fencing contractor looking to provide your customer with a compact gate closer solution for their new gate, the Easy Garden Gate Closer would be a natural choice. Other common OEM applications are with machine guarding (cage doors), kennels, shed doors, shutters and fly screens and the like.

The GCG2000 Easy Garden Gate Closer's popularity is driven by two things, quick and simple installation and value for money. It's one of the simplest gate closer installations you will find.

If you would like help with anything to do with this product, our telephone number and email address are at the bottom of this page.



Key features:

Simple to install

Adjustable closing speed

Adjustable final latch speed

Suitable for timber or metal gates & doors

90 degree opening angle

Gate weight up to 50 kg (max.)

Gate width up to 1.0 m (max.)

Gate height up to 1.8 m (max.)

Black powder coated steel housing


GCG2000BL Easy Garden Gate Closer - black

* CAUTION - GCG2000 Easy Garden Gate Closers are only suitable for installation where the gate post or door frame are flush with the gate or door and the hinge point is on the corner of the post or door (see installation instructions on next pages).



Suitable For 'T' and Butt Hinges Where Gate and Post Are Flush

This gate closer is specifically designed for installing to gates that are designed for two types of hinges, 'T' hinges and butt hinges. Examples of these hinges are shown in the drawings below.

Do **NOT** fit this gate closer to any gate that does not have suitable types of hinges or if the size, weight and dimensions are outside the range shown in the instructions.



Distance from face of post to centre of hinge must be **NO** greater than **6 mm**



INSTALLATION INSTRUCTIONS FOR GATE CLOSER

Maximum Gate Weight-50kg

Maximum Gate Width-1000mm

- The closer can be fitted to the top, middle or bottom of the gate on the "pull" side only.
- The gate face must be flush with the gatepost face and hinged as close as possible to the post.
- The pivot point of the closer must be in line with the pivot point of the hinges. It may be necessary to fabricate a bracket to allow the closer to be fitted correctly.
- The gate must swing freely on the hinges prior to fixing the closer and the hinges regularly greased.
- The guide roller must be fitted and it may be necessary to fabricate a bracket to receive the roller.
- The gate must not be allowed to open more than 90° and a ground stop must be fitted if required.
- The holding pin (see fig. 4) must not be removed until the closer is fitted.

